



Drop-in - Series Elegance - Cold Elements - Refrigerated top plate
MODELO DRTP-511

MODELO : _____
NOMBRE : _____
NOMBRE DE PROYECTO : _____
ZONA DE PROYECTO : _____
ARTICULO DE PROYECTO : _____



Drop-in - Series Elegance - Cold Elements - Refrigerated top plate

Model: DRTP-511


Reference	
Gas	R-134a
External dimensions (mm)	1765 x 610 x 558
Cut-out dimensions (mm)	1740 x 585
Capacity	5 GN 1/1
Power (W)	310

General characteristics

- Refrigerated top plate with cold unit included (Optionally elements can be supplied for connection to a remote refrigeration group.)
- Specially manufactured in high-quality stainless steel for intensive professional applications.
- Working surface recessed 10 mm below counter top.
- Control panel with intuitive digital control which allows temperature parameters to be adjusted easily and luminous start-stop light button.
- Tray with automatic evaporation of condensing water.
- Prepared for optional installation of a light foodshield, easily mounted on the structure by means of threaded plates.
- Static cooling made by pressed copper coil in the base of the plate isolated by CFC free, high density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Special clamps in the sides that ensure a uniform fit and grip over the entire surface.
- Rounded Edge interior and ½" Drain Valve in the bottom plate for easier cleaning operations. A connection from the drain to the sanitation network is compulsory.
- Operating temperature for refrigerated top plate (in climate Class IV conditions): 0°C to +8°C Versions with 2 refrigerant gases:
 - - R134a Hydrofluorocarbon (HFC).
 - - R600a Hydrocarbon (HC)
- Operating voltage and frequency: 230V 1N 50 Hz.

asber

Drop-in - Series Elegance - Cold Elements - Refrigerated top plate
DRTP-511



Packaging dimensions:
Height: 100 MM
Depth: 100 MM
Width: 100 MM
Gross weight: 74 KG



La compañía se reserva el derecho a realizar modificaciones en el producto sin notificación previa. La información actualizada se encuentra en la web

